

with GeoBubble™ technology



An innovative solution for water management

www.geobubble.co.uk www.VapourGuard.com


GeoBubble

Vapour Guard © Plastipack Ltd


Protect and conserve stored water

Water management is a growing concern for industry, agribusiness and domestic applications internationally, with a growing number of regions placing stress on their water supplies. With scarce resources, costly extraction and transportation costs, the need to secure and maintain a managed water storage system is both an economic and environmental necessity.


VapourGuard™ floating cover solutions are a useful, adaptable tool in the preservation and maintenance of water storage systems.



VapourGuard™ material provides evaporation control, algae inhibition, debris reduction and temperature regulation. The material can be applied in modular sections or as a complete covering membrane to the surface of the water. With the addition of small holes during the fabrication process the cover can also be used for rain water harvesting.



Manufactured by Plastipack Ltd the material is available in roll form, 2.5m wide with a 50mm salvage/weld edge in 90m lengths. The material can then be heat bonded into modular or amalgamated shaped cover by specialist fabricators to meet the required dimensions of the application.





The unique GeoBubble™ design and additive package of the Guard product range have been scientifically developed to provide higher performance and longevity of the blended polyethylene cover material. Providing a sustainable 100% recyclable (LDPE 4) and cost saving product which comes with a 6-year pro rata manufactures warranty

VapourGuard™ consists of 2 sheets of blended polyethylene to provide a strong

durable material. The material has air entrained cells for bouyancy and

insulation featuring the patented GeoBubble™ technology bubble profile.

- Eliminate water evaporation by 98%+
- **Harvest rain**
- Inhibit algae growth
- Reflect the sun's heat
- Reduce contamination
- 10 year pro-rata warranty
- With GeoBubble™
 Technology

The light grey top surface is highly reflective across the visible and near IR spectra, limiting solar gains and regulating the temperature of the water. The bottom layer in which the GeoBubble™ profile is formed is an opaque black layer. This prevents light penetration into the water body, blocking photosynthesis and inhibiting algae propagation under the cover. Manufactured by PLASTIPACK LIMITED



Specification Sheet

Polyethylene Film	Dual-Extruded
UV Protection	HALS
Colour	Light Grey / Black
Thermal Properties	Vicat Softening Point (1kg) 93°C
Cold Crack Temperature	-25°C
540 microns thickness	Bubble Film = 300 micron +/- 10% Back film = 240 micron +/- 10%
Weight per m²	520gms +/- 10%
Overall Bubble Width	2500mm +/- 1%
Welding Edges	50mm +/- 10%
Overall Width	2600mm +/- 10%
Roll Diameter	0.80m +/- 1%
Roll Length	90m +/- 2%
Est. Quantity for 120m³ truck	2.5m = 14,535m ² = 57 rolls
Est. Quantity Containers	$20 \text{ft} = 4,050 \text{m}^2 = 18 \text{ rolls}$ $40 \text{ft} = 10,125 \text{m}^2 = 45 \text{ rolls}$
Packaging	Packaged in Polyethylene bags
Core Diameters	Internal 76mm/External 80mm
Identification	Batch Identification by Q.A. slip and label showing Length/Grade
Warranty	10 year pro rata warranty
GEOBUBBLE™ TECHNOLOGY	
Bubble Width x Length	15x30mm
Bubble Height	5.5mm
No. of bubble per m²	1029

Water Storage: www.VapourGuard.com

Product information: www.GeoBubble.co.uk

Company Information: www.Plastipack.co.uk

Wainwright House, 4 Wainwright Close, Churchfields Industrial Estate, St Leonards-on-Sea, TN38 9PP UK t: +44 (0) 1424 851659 f: +44 (0) 1424 853909 e: info@plastipack.co.uk





